

Appl. No. 10/605,375

Amdt. dated 09/20/2005

Reply to Office action of 06/20/2005

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of the Claims

1. (currently amended) A shell for use in a subsurface borehole, comprising:
 - a composite body adapted to ~~cover~~ forming a cylindrical surface of revolution with an inner bore for housing a source or sensor, providing transparency to the passage of signals to or from said source or sensor, the composite body comprising a plurality of layers, at least one layer being substantially uniformly conductive along a single direction; and
 - a recess formed by the body extending from the inner bore toward the outer surface of the body;
 - a conductor element disposed within the recess;
 - wherein the body is adapted with a uniform conductive surface providing a path to short electric currents near the source or sensor.
2. (original) The shell of claim 1, wherein the body is adapted to provide transparency to the passage of electromagnetic signals.
3. (original) The shell of claim 2, wherein the body is formed to prevent direct exposure of the source or sensor to fluids within the borehole.

Appl. No. 10/605,375

Amdt. dated 09/20/2005

Reply to Office action of 06/20/2005

4. (original) The shell of claim 3, wherein the body forms a cylindrical surface of revolution with an inner bore adapted to house the source or sensor.
5. – 6. (canceled)
7. (original) The shell of claim 1, wherein the body comprises a composite graphite material including carbon particles disposed therein.
8. (original) The shell of claim 1, wherein the body comprises a carbon-loaded epoxy mixed with carbon fabric.
9. (original) The shell of claim 1, wherein the body comprises multiple prepreg graphite layers.
10. (original) The shell of claim 1, wherein the body comprises concentric layers of fabric including carbon particles disposed therein.
11. (original) The shell of claim 4, further comprising a second cylindrical surface of revolution disposed within the inner bore of the body in contact with the inner surface of the body, the second surface adapted to provide transparency to the passage of electromagnetic signals.

Appl. No. 10/605,375

Amdt. dated 09/20/2005

Reply to Office action of 06/20/2005

12. (original) The shell of claim 11, wherein the second surface of revolution comprises an opening along its cylindrical wall providing a channel between its inner bore and the inner surface of the shell body.
13. – 16. (canceled)
17. (original) The shell of claim 1, wherein the body is formed of carbon-loaded thermal plastic.
18. (currently amended) An apparatus for use in a subsurface borehole, comprising:
 - an elongated support;
 - an antenna disposed on the support, the antenna adapted to transmit or receive electromagnetic energy; and
 - a composite shell forming a sleeve disposed on around the support and having an inner bore to house~~cover~~ the antenna, the shell providing transparency to the passage of electromagnetic energy, the composite shell comprising a plurality of layers, at least one layer being substantially uniformly conductive along a single direction;
 - the sleeve including a recess extending from the inner bore toward the outer surface of the sleeve; and
 - a conductive element disposed within the recess;wherein the shell is adapted with a uniform conductive surface providing a path to short electric currents near the antenna.

Appl. No. 10/605,375

Amdt. dated 09/20/2005

Reply to Office action of 06/20/2005

19. (cancel)
20. (currently amended) The apparatus of claim ~~18~~19, further comprising a conductor coupled to the sleeve to pass electric current through the sleeve and into said inner bore.
21. (original) The apparatus of claim 20, wherein the elongated support consists of a metallic tubular and the conductor coupled to the sleeve to pass electric current is coupled to said tubular.
22. (Original) The apparatus of claim 18, wherein the sleeve comprises a composite graphite material including carbon particles disposed therein.
23. (original) The apparatus of claim 18, wherein the sleeve comprises a carbon-loaded epoxy mixed with carbon fabric.
24. (original) The apparatus of claim 18, wherein the sleeve comprises multiple prepreg graphite layers.
25. (original) The apparatus of claim 18, wherein the antenna comprises a plurality of coils having non-parallel axes.

Appl. No. 10/605,375

Amdt. dated 09/20/2005

Reply to Office action of 06/20/2005

26. (canceled)
27. (original) The apparatus of claim 18, wherein said antenna is disposed on said support with its axis at an angle with respect to the support axis.
28. (currently amended) The apparatus of claim ~~18~~19, further comprising a second sleeve disposed within the inner bore of the composite sleeve in contact with the inner surface of said sleeve, the second sleeve adapted to provide transparency to the passage of electromagnetic energy.
29. (original) The apparatus of claim 28, wherein the second sleeve comprises an opening along its wall providing a channel between its inner bore and the inner surface of the outer sleeve.
30. – 32. (canceled)
33. (original) The apparatus of claim 18, wherein the sleeve is formed of carbon-loaded thermal plastic.
34. (currently amended) An apparatus for use in a subsurface borehole, comprising:
an antenna adapted to transmit or receive electromagnetic energy;

Appl. No. 10/605,375

Amdt. dated 09/20/2005

Reply to Office action of 06/20/2005

a composite shell ~~covering~~ forming a sleeve having an inner bore to house the antenna,
the shell providing transparency to the passage of electromagnetic energy, the
composite shell comprising a plurality of layers, at least one layer being
substantially uniformly conductive along a single direction;
the sleeve including a recess extending from the inner bore toward the outer surface of
the sleeve;
a conductive element disposed within the recess;
wherein the shell is adapted with a uniform conductive surface providing a path to short
electric currents near the antenna; and
a conductor coupled to the shell to pass said electric currents through said shell.

35. (original) The apparatus of claim 34, wherein the shell comprises a composite graphite material including carbon particles disposed therein.
36. (original) The apparatus of claim 34, wherein the shell comprises a carbon-loaded epoxy mixed with carbon fabric.
37. (original) The apparatus of claim 34, wherein the shell comprises multiple prepreg graphite layers.
38. (original) The apparatus of claim 34, wherein the antenna comprises a plurality of coils having non-parallel axes.

Appl. No. 10/605,375

Amdt. dated 09/20/2005

Reply to Office action of 06/20/2005

39. - 40. (canceled)

41. (currently amended) The apparatus of claim 3440, further comprising a second sleeve disposed within the inner bore of the composite sleeve in contact with the inner surface of said sleeve, the second sleeve adapted to provide transparency to the passage of electromagnetic energy.

42. (original) The apparatus of claim 41, wherein the second sleeve comprises an opening along its wall providing a channel between its inner bore and the inner surface of the outer sleeve.

43. - 45. (canceled)

46. (original) The apparatus of claim 34, wherein the shell is formed of carbon-loaded thermal plastic.